



609-259-8900
 609-259-3575 (fax)
 nj.sales@mcmaster.com



Certificate

Purchase Order PO26101646	Order Date 3/12/2026	Placed By Christopher Berger	McMaster-Carr Number 4162462-01	Number of Certificates 1
-------------------------------------	--------------------------------	---	---	------------------------------------

Line	Product	Ordered	Status	Certificate
15	90327A113 Alloy Steel Low-Profile Socket Head Screws, Hex Drive, Zinc Plated, M4 x 0.7 mm Thread, 10 mm Long	1 pack	1 pack delivers March 16	292-9890

Sales Order Number: 1352018-002
 Finished Lot Number: 4197862-PPO



LAB OFCO

No.181, Ziqiang Ln., Siwei Rd., Ziguang Dist., Kaohsiung City 82649, Taiwan
 TEL:886-7-612-5899 FAX:886-7-612-5789

CERTIFICATE OF INSPECTION DIN EN 10204:3.1

REPORT NO.	:LIND1140725002	LOT NO.	:A09161
INSPECTION DATE	:20250522	HEAT NO.	:07815
SAMPLE PLAN SPEC	:ISO 3269-2019	MATERIALS	:10B33
CUSTOMER	:LINDSTROM, LLC		
ADDRESS OF CUST	:2786 SPECTRUM DRIVE Elgin IL 60124		
INVOICE NO.	:OF-072825-80	P.O.NO.	:00929139
MANUFACTURED BY	:OFCO	ORDER QUANTITY	:110000 PCS
MANUFACTURING DATE	:20250430	SHIPPED QUANTITY	:110000 PCS
DESCRIPTION	:DIN 7984-8.8	HEAD-MARK	:
SIZE	:M4-0.7X10mm	HT/PLAIN	
SAMPLER	:LIU CHIH HAO	ARTICLE NO.	:LHS4804010

LHS4804010
 Lot # Z091000440
 Lot

1.MATERIAL :

STEEL MAKER (HEAT NO.)	CHEMICAL COMPOSITION%											
	C X100	Si X100	Mn X100	P X1000	S X1000	Cu X100	Ni X100	Cr X100	Mo X100	V X100	B X10000	A1 X1000
07815	34	21	85	16	1						20	

2.DIMENSIONS OF SPEC :

SPECIFICATION : DIN 7984-2022

UNIT : mm

TEST ITEM	SPECIFICATION	SPECIFICATION	SAMPLING	REJ	REMARK
APPEARANCE	ISO 6157-1	OK-OK	32	0	
HEAD HEIGHT	2.66~2.80	2.75~2.78	8	0	
HEAD DIAMETER	6.78~7.00	6.82~6.85	32	0	
WIDTH ACROSS FLATS	2.52~2.60	2.55~2.60	32	0	
WIDTH ACROSS CORNERS	2.87(MIN)	3.08~3.13	8	0	
MAJOR DIAMETER	3.838~3.978	3.85~3.88	32	0	
GRIP LENGTH	2.10(MAX)	0.69~0.72	8	0	
NOMINAL LENGTH	9.71~10.29	10.06~10.09	32	0	
HEX SOCKET DEPTH	2.18~2.42	2.25~2.40	8	0	
dw	6.20(MIN)	6.20~6.21	8	0	
POINT LENGTH	1.40(MAX)	0.62~0.66	8	0	
R	0.20~0.35	0.22~0.23	8	0	
THREAD	GO/NO GO	OK-OK	32	0	

3.MECHANICAL PROPERTIES

SPECIFICATION : ISO 898-1:2013(E), DIN 7984-2022

TEST ITEM	TEST METHOD	STANDARD	RESULT	SAMPLING	REMARK
CORE HARDNESS(HV)	ISO 6507-1	250-320	292.4 291.5 292.8	3	OK
TENSILE LOAD (N)	ISO 898-1	5620(MIN)	6,205 6,127 6,243	3	OK
DECARBURIZATION TEST	ISO 898-1	0.015(MAX)	0 0	2	OK

Hsin-Tung Hsieh

SIGNATORY

2025.07.25

(DATE)

QUALITY ASSURANCE MANAGER

*INSPECTION RESULT : SAMPLES TESTED CONFORM TO ALL OF SPECIFICATION ABOVE.
 *THIS TEST REPORT CAN NOT BE REPRODUCED EXCEPT IN FULL WITH THE WRITTEN APPROVAL OF THE LAB.MANAGER.
 *THE PRODUCTS SUPPLIED ARE IN COMPLIANCE WITH THE REQUIREMENT OF ORDER.
 *Country of Origin : Taiwan