



562-692-5911  
562-695-2323 (fax)  
la.sales@mcmaster.com



# Certificate

<b>Purchase Order</b> PO26191751	<b>Order Date</b> 5/15/2026	<b>Placed By</b> Christopher Berger	<b>McMaster-Carr Number</b> 7498672-02	<b>Number of Certificates</b> 1
-------------------------------------	--------------------------------	---	---	------------------------------------

Line	Product	Ordered	Status	Certificate
2	8982K522 Multipurpose 6061 Aluminum 90 Degree Angle with Square Leg Edge, 1/8" Wall Thickness, 3" Outside Width, 2 Feet Long	1 each	1 each delivers May 18	329-2145



**Service Center Metals**  
 5850 Quality Way  
 Prince George, VA 23875



**CERTIFIED INSPECTION REPORT AND TEST RESULTS  
 FOR EXTRUDED PRODUCTS**

<b>BILL TO</b>	<b>MANIFEST NUMBER</b>	<b>DIE NUMBER</b>	<b>DATE OF SHIPMENT</b>
A. M. Castle and Company	634292	AUA1226	1/12/2026
<b>SHIP TO</b>	<b>CUSTOMER PO</b>	<b>ALLOY / TEMPER</b>	<b>SALESPERSON</b>
Castle Metals-Janesville	695568	6061-T6	David Schroeder
<b>Quantity Certified</b>	<b>CUSTOMER PART NUMBER</b>	<b>DESCRIPTION</b>	
1,110 lbs	SA1248595	AUA 3.000X2.000X.125	

<b>OUR ORDER NUMBER</b>	<b>ITEM</b>
1205484	1
<b>CERTIFICATION</b>	
ASTM-B308-20 SPOT STEN	
<b>SPECIFICATION</b>	
SAE AMS-QQA-200/8A Stabilized	
<b>SPECIFICATION</b>	
ASTM-B221-21	

We hereby certify that the material covered by this report has been inspected in accordance with the most recent certification revision, and has been found to meet the applicable requirements described herein, including any specifications forming a part of the description, and that samples representative of the material meet the composition limits and had the mechanical properties shown.

All aluminum products supplied by Service Center Metals, LLC contain no functional mercury. Neither mercury nor its compounds are used in the manufacture of aluminum products at our facility. Furthermore, aluminum products supplied by Service Center Metals have not, to the best of our knowledge, contacted any source of mercury. This material was not exposed to any radioactive source. Items produced and certified as 6061-T6511 also meet the requirements of 6061-T6.

This product is RoHS-3, REACH, and DfARS compliant.

**SCM is ISO 9001-2015 certified**

**Mechanical Properties**

Tests	Lot No.	Test Date	Ultimate Tensile Strength (KSI)		Yield Strength (KSI)		Percent Elongation	
			min	max	min	max	min	max
2	202600036	1/9/26	43.70	43.90	40.50	40.80	11.50	12.20

**Chemical Composition for Aluminum Alloy 6061**

Cast #	Lot No.	Alloy	Others										Melt Source:	
			Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Al	Each		Total
218C260101A	202600036	6061	0.61	0.28	0.19	0.07	0.84	0.06	0.03	0.02	97.90	0.05	0.15	USA (SCM) secondary



SCM products are melted and extruded in the USA

Michael Deitrick, QA & Technical Manager

Print Date: 1/13/2026