



562-692-5911  
562-695-2323 (fax)  
la.sales@mcmaster.com



Certificate

|                                     |                               |                                           |                                           |                                    |
|-------------------------------------|-------------------------------|-------------------------------------------|-------------------------------------------|------------------------------------|
| <b>Purchase Order</b><br>PO26311865 | <b>Order Date</b><br>8/3/2026 | <b>Placed By</b><br>Christopher<br>Berger | <b>McMaster-Carr Number</b><br>3407885-01 | <b>Number of Certificates</b><br>1 |
|-------------------------------------|-------------------------------|-------------------------------------------|-------------------------------------------|------------------------------------|

| Line | Product                                                                                        | Ordered | Status                   | Certificate |
|------|------------------------------------------------------------------------------------------------|---------|--------------------------|-------------|
| 5    | 92095A181 18-8 Stainless Steel Button Head Hex-Drive Screw, M3 x 0.5 mm Thread Size, 8 mm Long | 1 pack  | 1 pack delivers August 5 | 361-7492    |



# 華 祺 工 業 股 份 有 限 公 司 RODEX FASTENERS CORP.

NO. 29 SUNG CHIANG NORTH RD. CHUNG LI IND. PARK 32062, TAIWAN.  
TEL: 886-3-4529606 4511493 FAX: 886-3-4529546 4520861  
WEBSITE: <http://www.rodex.com.tw>  
E-MAIL: [rodex@ms11.hinet.net](mailto:rodex@ms11.hinet.net)

**ISO 9001**  
REGISTERED  
CERT NO. 4M4Y003

## CERTIFICATE OF INSPECTION

**PURCHASER:** WURTH INDUSTRY USA (REVCAR)

**CERT NO:** Q25120876

**PO# NO.:** 20547902

**DATE:** 2025/12/29

**ITEM:** ISO7380 HEX BUTTON HEAD SOCKET SCREW SUS 304 (A2) / M3X8 / FULL THREAD

**PART NO.:** 4SKBA23C8-ISO7380-BAG100

**QUANTITY:** 585.00

**MPCS**

**SAMPLE SIZE:** 13

**PCS**

**PROD NO.:** I14C132-001

**UNIT:** MM

**LOT NO.:** I14C132-001

**SHIPMENT QY.:** 590.60 **MPCS**

**INVOICE NO.:** IV2601068

**SAMPLE PLAN SPEC.:** MIL-STD-105E

### **DIMENSIONAL INSPECTIONS**

### **SPECIFICATION : ISO7380**

| CHARACTERISTICS                | SPECIFICATION | ACTUAL RESULT | Acc. | Rej. |
|--------------------------------|---------------|---------------|------|------|
| Head Diameter                  | 5.40 ~ 5.70   | 5.54 ~ 5.57   | 13   | 0    |
| Head Height                    | 1.40 ~ 1.65   | 1.51 ~ 1.53   | 13   | 0    |
| Major Diameter                 | 2.88 ~ 2.98   | 2.93 ~ 2.94   | 13   | 0    |
| Tolerance On Length            | 7.71 ~ 8.29   | 7.93 ~ 8.00   | 13   | 0    |
| Ring Gauge (Go & Not Go Gauge) |               | Passed        | 13   | 0    |
| Key Engagement Min             | 1.04          | 1.13          | 13   | 0    |

### **CHEMICAL COMPOSITION (wt%)**

| HEAT<br>NUMBER | Cr<br>x100 | Cu<br>x100 | Mn<br>x100 | Mo<br>x100 | N<br>x10000 | Ni<br>x100 | P<br>x1000 | S<br>x1000 | Si<br>x100 | C<br>x1000 |
|----------------|------------|------------|------------|------------|-------------|------------|------------|------------|------------|------------|
| 7F289          | 1717.00    | 283.00     | 180.00     | 23.00      | 147.00      | 801.00     | 35.00      | 1.10       | 34.00      | 16.00      |

### **REMARK:**

**SECTION CHIEF:** C.H Yeh

**INSPECTED BY:** Melodie